



ALWAYS A WAVELENGTH AHEAD.



TX-1A
TOP

DESCRIPTION

The active 2-way full range top TX-1A is appropriate, when easy handling and a high performance at lowest dimensions is demanded.

The first class sound quality of the high-definition high frequency driver, combined with the powerful low-mid unit, results in an unbeatably audiophile combination. The TX-1A qualifies ideally for stages, installations or any conceivable mobile application in the full range or system operation.

A high BL product takes care of the acceleration for the hardened 10" conical diaphragm, to satisfy the elevated requirements of a precise impulse response. The stretched elliptical CD-horn excels by its long throw.



FEATURES

Despite of the compact dimensions, the TX-1A a round bracing to exclude mechanical vibrations. Perfect acoustic damping promises the usage of genuine sheep's wool.

- Coherent Wavefront Design
- Perfect coverage
- Outstanding dynamic
- Intelligent rigging hardware EPS
- DSP controlled amplifying unit
- Adjustable tilt angle flange mount



APPLICATIONS

With three integrated EPS (Express Pin System) points the TX-series can be rigged in countless varieties. The timesaving mounting is done with just one handle.

- Portable PA for bands / DJs
- Clubs / Discos
- DJ- & stage monitor
- Speech reinforcement
- Sidefill / Drumfill
- Gala events



PERFORMANCE

System Configuration	High power 2-way fullrange top 1 x 10" high excursion 3" VC driver 1 x HF-compression driver with 1.75" VC polyester diaphragm
Electronics	800W + 200W RMS amping power
Signal Processor	24bit ADC/DAC, 48kHz samplerate
Frequency Response	70-20000Hz (+/- 3dB)
Coverage Angle	80° horizontal x 55° vertical
Monitor Angle	24° / 44°
Crossover Frequency	1400Hz
Sensitivity	96dB / 1W / 1m
Connection	XLR in / out, Powercon in / out



PHYSICAL

Enclosure	Rigid braced construction of special 12mm lightweight-wood	
Finish	High-density polyurethane-coating Black	
Front Cover	Weather-resistant front fabric on coated 1.5mm perforated steel	
Dimensions	Inches	Millimeters
Height	21.3	541
Width	12.8	324
Depth	13.3	339
Weight	Pounds	Kilograms
	33.9	15.4

